



ergoCentric
 SEATING • SYSTEMS

The Ergo 2F Series supports the tasks required at raised work stations, while increasing comfort, health, and productivity. The easily adjustable footring supports the user's legs for various height requirements so that problems including fatigue, poor posture and decreased circulation can be avoided.

The Ergo 2F can also be specified to meet clean room standards, meeting the cleanliness specifications for:

- Federal Standard 209E, Class 1, 10, 100 & 1000 environments.
- ISO 14644-1 Class 3, 4, 5 & 6 environments.

Adjustment Options:



Standard Control

- 30° back angle adjustment
- 4.5" back height adjustment
- 30° back pivot

Multi Tilt Control

- 20° back angle adjustment
- Back height adjustment
- 6-10° seat angle adjustment with forward tilt
- Free float with infinite lock

- Forward tilt lockout
- Tilt tension control
- 3" back bar housing
- Pneumatic height adjustment

Seat Options:



Standard: 17" W x 18.5" H
Extra Small: 17.5" x 15.5"
Large: 20" x 19"

Memory Foam Seat
Triple Density Foam Seat (Adds 1/4")

Armrest Options:



T-Arms

- Polyurethane arm pad 4" W x 10.5" L
- Solid 1/4" thick spring steel frame, epoxy powder coated black

- Arm height from seat pan 7.5"
- Optional black Nyvek upholstered arm pad



3 Inch Adjustable T-Arm

- Finger tip adjustment
- Polyurethane arm pad 3" W x 10.5" L
- Solid 1/4" thick spring steel frame, epoxy powder coated black

- Arm height adjustable from seat pan 6" - 10"
- Arms width adjustable 2" per arm
- Optional black Nyvek upholstered arm pad

Pneumatic Lift Options:



80mm, 13.75"-16.75"
 100mm, 14"-17.5"
 125mm, 25.5"-19.5"
 157mm, 16.25"-22.25"

Base Options:



Nylon Reinforced Base

Footring Options:



Footring


PAC Midwest
 Minneapolis, MN
 (888) 903-0333

PAC South
 Dallas, TX
 (800) 442-4008


PAC West
 Los Angeles, CA
 (888) 839-3936

PAC Mexico
 Tecate, Mexico
 (619) 573-4501

Caster Options:



2" Nylon Dual Wheel Caster
 Designed for use on carpet.



2" Urethane Dual Wheel Caster
 Designed for use on hard floor, tile, concrete & marble floors.



2.5" Single Wheel Caster
 Designed for use on heavy carpet.



2.5" Single Wheel Urethane Caster
 Designed for use on rough floor surfaces.



3" Single Wheel Urethane Casters
 Designed for use on rough floor surfaces.
 Adds 2.5" to seat height.



2.25" Lock On Urethane Double Wheel Braking Casters
 Provides the stability of glide and mobility of a caster. When the user's weight is on the chair, the wheels lock. With no weight on the chair, the caster unlocks and moves freely.



2.25" Lock Off Urethane Double Wheel Braking Casters
 Ideal for use on tile floors. When the user's weight is off the chair, a brake is applied to prevent the chair from rolling away.



1.25" Glides (Standard)
 Provides stability for use on commercial carpet floors.



2.25" Glides
 Provides stability for use on commercial carpet floors.