



MATERIALS:

Receptacle — 18-8, type-304, 22-gauge (0.8mm) stainless steel with satin finish. Bottom edges are hemmed. Equipped with four spot-welded interior hooks for attaching the vinyl liner. Stainless steel straps on back of unit reinforce the four mounting screw holes. Capacity: 20-gal. (75.7-L).

Liner — Heavy-gauge vinyl with four grommets. Removable for servicing.

OPERATION:

Removable vinyl liner attaches to four interior hooks of waste receptacle. Bottom edges are hemmed for maximum safety. Space between bottom of receptacle and floor when unit is mounted on wall facilitates floor cleaning.

INSTALLATION:

Mount unit to wall with four sheet-metal screws furnished by manufacturer at points indicated by an S. For plaster or dry wall construction, provide concealed backing to comply with local building codes and secure with screws furnished. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.

SPECIFICATION:

Surface-mounted waste receptacle shall be type-304, 22-gauge (0.8mm) stainless steel. Exposed surfaces shall have satin finish. Waste receptacle shall be equipped with four interior hooks, have reinforced mounting screw holes, and shall be furnished with a removable heavy-gauge vinyl liner. Unit shall have a capacity of 20-gal. (75.7-L).