



Cut



Light Duty

Best in-class protection and performance with unmatched comfort

- The HyFlex® 11-318 brings a new degree of dexterity to applications with cut risks: it is the first uncoated glove to provide EN Level 3 cut protection in an 18 gauge liner.
- Its ultra light fabric creates a sensation of bare hand contact and helps to maintain the hand at a comfortable working temperature.
- It offers a snug/ergonomic fit on the hand thanks to the spandex reinforcement in the tension areas of the hand (knuckles and palm).
- This low lint glove is also silicone free and anti-static to ensure worker and product protection. Furthermore a specific packaging was developed in order to prevent silicone contamination from plastic bags.

Industries

- Automotive
- Machinery and Equipment
- Chemical

Applications

- Handling parts with sharp, rough edges
- Assembly & inspection of components
- Inspection of parts, equipment
- Body Surface checking, marking and touching up
- Final inspection
- Inspection (picking, checking and marking)
- Maintenance



Key Features

- Light weight uncoated liner maintains worker comfort while delivering protection against lacerations and high tactility
- Process safe : Silicone Free, Anti-Static, and low linting
- Touch screen compatible design

Technologies



Performance Standards & Regulatory Compliance



REACH Compliant

Specifications

BRAND STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	PACKAGE
HyFlex® 11-318	, N/ A, Dyneema® Diamond Technology, Knitwrist	18	6, 7, 8, 9, 10, 11	212-260 mm/ 8.35-10.24 inches	• 12 pairs/polybag; 12 polybags/carton; 144 pairs/carton

