

VersaTouch

88-394

Mediumweight, unlined natural rubber glove

A combination of great protection and a high level of dexterity, makes this glove Ideally suited for the food processing industry

- Excellent dexterity, tensile strength and elasticity
- 20 mil thickness provides good chemical, snag, puncture and abrasion resistance
- Fishscale pattern designed for excellent grip on wet or dry surfaces



Industries

- Food processing

Applications

- Fruit and Vegetable Processing
- Canning
- All food processing applications that have food contact
- Clean room cleaning and preparing

VersaTouch

88-394

Mediumweight, unlined natural rubber glove

Key Features

- Medium duty glove
- FDA food compliance

Performance Standards



EN 388:2016



1010X

EN 388:2003



2110

EN ISO 374-5



CHEMICAL AGENT	BREAKTHROUGH TIME
Sodium hydroxide, 40% (K)	>480

PERMEATION BREAKTHROUGH TIMES ACCORDING TO EN 16523-1 : 2015 (MINUTES)						
0	1	2	3	4	5	6
< 10	10-30	30-60	60-120	120-240	240-480	> 480
Not recommended	Splash protection		Medium protection		High protection	

Data given in the table above are based on results of laboratory tests performed on the palm area of the glove. These tests were run using standard test methods that may not adequately replicate any specific conditions of end use. Because Ansell has no detailed knowledge or control over the conditions of end use, any of these data must be advisory only, and Ansell must decline any liability.

Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
VersaTouch® 88-394	Natural Latex Rubber,	7, 8, 9, 10	299 mm, 12"	Natural	• 12 Pairs Per Bag; 12 Bags Per Case