



Extra-Large Deep-well Digital Solder Pot Model: D-1400



Product Overview

Compare to Plato SP600.

Last year, American Beauty Tools made its long awaited entry into Digital, Mil-Spec Compliant Solder Pots. This year, we've added Large & Extra Large Deep pots to that family. Available in ALL SIZES, we have combined our reputation for rugged durability with the latest in precision temperature control technology. Easily exceeding the tightest of military standards.

Features and Benefits

Mil-Spec Compliant - Exceed the requirements of military specifications ANSI(J-STD-0018)

Digital LCD temperature displays both preset and actual temperature in °F or °C

Pot controls temperatures to $\pm 5^{\circ}\text{F}$ ($\pm 2.75^{\circ}\text{C}$) of a preselected setting, from ambient to 925°F.

Limits transient voltage spiking for voltage sensitive components (2.5mV) Internal circuitry is adaptive to input voltage power fluctuations.

Technical Specifications

Wattage	1400 watts
AMP Draw	< 13 Amp
Temperature Range	350-925 °F / 177-496 °C
Temperature Variation from Set Point	5

Available in a 220-240 VAC?	Yes, available upon request
Net Volume	Approximately 25-36 pounds of solder, dependent upon alloy.
Solder Bath Depth	6" by 4" by 4" in
Product Length	7.75 in / 19.69 cm
Product Width	14.75 in / 37.47 cm
Product Height	10.25 in / 26.04 cm
Product Weight	38 lbs / 17.24 kg
Package Dimensions (Inches)	16 x 10 x 12
Package Weight	40 lbs / 18.14 kg
Country of Origin	US
Harmonization Code:	8515.11.0000
RoHS Compliant	Yes
IEC 60335-1, Edition 5.1, 2013-12	Yes
WEEE Compliant	Yes
CE Certified	Yes
Instruction Sheet (PDF)	Instruction Sheet
Warranty Policy	Details
User Manual	User Manual

Similar Products

The following products are related (similar model but different specifications, etc.) to Model D-1400 featured on this page:

Model	Product Name
D-900	Large Deep-well Digital Solder Pot

End-Of-Life Instructions

In an effort to reduce waste and comply with WEEE directive, please do not dispose of product. All American Beauty Tools are serviceable and can be repaired and/or replaced. Please contact manufacturer to make arrangements.