





SHOWA

3415

The pinnacle of protection, comfort and dexterity, SHOWA 3415 creates a defensive barrier between you and a range of chemicals, including acids, caustics, solvents, grease and oil.

FEATURES

- Fully-coated neoprene
- 15 gauge seamless knit liner14" (355mm) gauntlet
- Rough particle grip



- Flexible, consistent film coating
- Protection against a wide range of chemicals, including acids, caustics, solvents, grease and oil
- Prevents irritation
- Tactile non-slip grip

INDUSTRY



Chemical



Manufacturing



Oil and Gas



Utilities

IDEAL APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Component Assembly
- Deck crew
- Digging
- Drilling
- Pipe Fitters
- Plumbing
- Water/Sewage treatment



TAA PRODUCTS

MATERIAL

- Polvester
- Seamless knit

COATING

- chemical resistant
- Neoprene
- Water resistant

GRIP

Rough

STANDARDS

Cat. III



0321 EN I<u>SO 374-5:</u>2016







SHOWA

3415



PACKAGING

- 12 Pair Per Carton6 Cartons Per Case
- 72 Pair per case



SIZES

- **խ** §
 - M
 - XL



COLOUR

Black



YOU MIGHT ALSO BE INTERESTED IN





MATERIAL
Cotton
COATING
chemical
resistant





MATERIAL
Engineered yarn
COATING
chemical
resistant

379



MATERIAL
Polyester
COATING
chemical
resistant

USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



