

SHOWA

234

Gray

Foam nitrile palm coating over spandex/engineered cut resistant liner reinforced with HPPE

[FEATURES

- 15 gauge seamless knit spandex liner with HPPE
- Foamed flat dipped coating with sponge finish for good grip
- ANSI/ISEA 105-16: Level A4 (minimum 1500g)
- EN 388:2016 Cut Level D
- Contact Heat level 2
- FDA & EU Food Contact approved
- Lightweight, supple liner with breathable open back design

[BENEFITS

- Resilient cut resistant glove offering excellent grip and cut protection in dry & greasy environments
- Excellent cut resistance performance - ANSI level A4 and EN 388:2016 level D
- Foam nitrile coating protects against oils, hydrocarbons, grease and abrasions, while offering excellent grip in wet and dry conditions
- Cooling HPPE properties and breathable back of hand reduces perspiration and keeps hands dry
- Thin and lightweight for enhanced dexterity and longer use
- Ergonomically designed to replicate the hand's natural curves
- Launderable for re-use, leads to less waste and cost efficiency
- Seamless knit designed to prevent irritation

[INDUSTRY



Automotive



Construction



Food



Glass



Manufacturing



Warehousing and Distribution

[IDEAL APPLICATIONS

- Light assembly of oil-coated pieces
- HVAC
- Maintenance
- Mechanical and engineering
- Repair glass and windows
- Steel fabrication
- Washing & cleaning
- Component Assembly



TAA PRODUCTS

MATERIAL

- HPPE

COATING

- Nitrile

GRIP

- Foam

STANDARDS



SHOWA

234

Gray



PACKAGING

- 12 Pair per polybag
- 72 Polybags per case
- 144 Gloves per case



COLOUR

- Gray



SIZES

- S
- M
- L
- XL
- XXL



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
4561



MATERIAL
Kevlar
COATING
Foam nitrile

SHOWA
257



MATERIAL
Aramid knit
COATING
Foam nitrile

SHOWA
546



MATERIAL
Engineered yarn
COATING
Polyurethane

SHOWA
S-TEX 581



MATERIAL
Kevlar
COATING
Foam nitrile

[USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved