

SHOWA  
**3416**

Combining the best of cut and chemical-resistant technology, SHOWA 3416 provides ANSI level A5 and EN level 5 cut protection and first-class defense against acids, caustics, solvents, grease and oil. Constructed with a seamless knit liner for maximum comfort and endurance, this fully coated neoprene gauntlet is always ready for action.

**[ FEATURES**

- 13-gauge seamless cut-resistant engineered fiber
- Fully coated neoprene
- 355 mm (14 in.) gauntlet
- Rough particle finish

**[ BENEFITS**

- ANSI Cut Level A5
- EN Cut Level 5
- Protection against a wide range of chemicals, including acids, caustics, solvents, grease and oil
- Flexible coating with maximum comfort and protection
- Tactile non-slip grip

**[ INDUSTRY**



**Chemical**



**Glass**



**Municipal Services**



**Oil and Gas**

**[ IDEAL APPLICATIONS**

- Chemical spray and treatment
- Coating preparation
- Handling glass and windows
- Window manufacturing
- Deck crew
- Drilling
- Handling heavy equipment



**TAA PRODUCTS**

**MATERIAL**

- Engineered yarn
- Glass Fiber
- HPPE
- Polyester
- Seamless knit

**COATING**

- chemical resistant
- Neoprene
- Water resistant

**GRIP**

- Rough

**STANDARDS**



SHOWA  
**3416**



**PACKAGING**

- 12 Pair Per Carton
- 6 Cartons Per Case
- 72 Pair per case



**COLOUR**

- Black



**SIZES**

- S
- M
- L
- XL



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**3415**



**MATERIAL**  
Polyester  
**COATING**  
chemical resistant

SHOWA  
**379**



**MATERIAL**  
Polyester  
**COATING**  
chemical resistant

SHOWA  
**CHM**



**MATERIAL**  
Coton flock  
**COATING**  
chemical resistant

SHOWA  
**VMU**



**MATERIAL**  
Unsupported  
**COATING**  
Latex

**[ USER INSTRUCTIONS**

Protection against mechanical risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

**SHOWA USA** | 579 Edison Street - Menlo, GA 30731, USA  
**USA@SHOWAGroup.com**

© SHOWA Group 2018 | All rights reserved