



## Electrically Conductive Anti-Fatigue, Diamond-Plate Anti Fatigue Mats

### Group 786-DP

Electrically Conductive Anti-Fatigue is our #1 seller year in and year out for static control applications. Perhaps it's because the mat so effectively protects sensitive equipment while dramatically reducing standing fatigue. Or perhaps it's because the mat is so remarkably durable and features our top of the line Nitricell sponge. Or maybe it's that Electrically Conductive Anti-Fatigue outlasts and outperforms every copycat mat [yes, Wearwell came first], providing the best long-term value for ESD applications.

Whatever the reason, you can rest assured that this mat will always live up to high expectations...like any seasoned All-Pro player. It's a winner!

NOTE: Mats must be grounded with a ground cord ([793-Cord](#)) and users must wear a heel grounder ([793-Heel](#))

- "Best" sponge base
- NFSI Certified
- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges
- Available in Smooth and Diamond Plate surface pattern
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness, Standard 9/16" (14 mm) or UltraSoft 15/16" (24 mm)
- Grounding snap is attached to the corner of each mat (NOTE: Mat must be grounded with a ground cord; workers must wear Heel Grounder or shoes with conductive soles)

**Type** Anti-Fatigue Matting

**Suitable Environment** Dry

**Customization Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** PVC Surface With Nitrile Infused Sponge

**Recycled** <10%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1000g, CS-17 wheel
Temperature Range	-10 to 130 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90
Compression Deflection	ASTM D575 / Deflection @35 psi, mm=8.43
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: $1 \times 10^3 - 1 \times 10^6$
Dielectric Strength	Not Available

SKU	UPC	Color	Diameter	Dimensions	Stock Part	UOM
786.1516x2x3DPBK	715411040612	Black	0.9375	2' x 3'	Y	EA
786.1516x3x5DPBK	715411040629	Black	0.9375	3' x 5'	Y	EA

786.1516x3x75DPBK	715411040636	Black	0.9375	3' x 75'	N	RL
786.1516x4x75DPBK		Black	0.9375		N	RL
786.916x2x3DPBK	715411607044	Black	0.5625	2' x 3'	Y	EA
786.916x3x5DPBK	715411603541	Black	0.5625	3' x 5'	Y	EA
786.916x3x75DPBK	715411609659	Black	0.5625	3' x 75'	N	RL
786.916x4x75DPBK	715411001903	Black	0.5625	4' x 75'	N	RL