



American Hakko Products, Inc.

PRODUCT BULLETIN

Bulletin No: PB391

Issue Date: 7-12-2016

Available: 7-25-2016

Product Description:

NEW HAKKO C5029 Handpiece Fixture (L)

Part No:

C5029



Specification:

Part No.	C5029
Reach¹	131 mm (5.15 in.) Max
Z-axis Stroke	120 mm (4.7 in.)
Arm Position	Adjustable through 180°
Dimensions (W x H x D)	582 x 491 x 361 (22.9 x 19.3 x 14.2 in.)
Weight (L)	8.89 kg (19.6 lbs.)
ESD Safe	Yes

¹ - Measured with C5027 Board Holder

Contents:

Part No.	Description
C5029	Hand Piece Fixture L
--	O-Ring
888-085	Hex Wrench (6 mm)
--	User Manual

Comments:

The HAKKO C5029 Handpiece Fixture is designed for use with the HAKKO FR-810 and FR-810B Hot Air Rework Stations, and the HAKKO FR-811 SMD Rework Station. The C5029 handpiece fixture provides large stable platform with multiple mounting positions for the HAKKO C5027 Board Holder. The fixture includes a one-touch slide adjustment as well as a knob for fine adjustment in the y-axis. The swing arm and adjustable collar of the fixture allows for easy positioning of the handpiece directly above the component to be reworked and also allows the rotation of the handpiece to adjust the theta angle of the nozzle in relation to the component. A component tray is also integrated with the handpiece fixture as an added swing arm that is height adjustable.

For more information, please visit us at www.HakkoUSA.com