

STAT PRO 3D PRINTING FILAMENT DRY CABINET MODEL NO. AW-3D80P



Specifications of AW-3D80P



Digital hygrometer

Automatic Electronic Drying Unit



RH Range	≤10%RH±5%RH, FRT<2HRS
External Dimensions	W54.0 x H 47.0 x D 41.0 cm W21.26x H 18.5 x D 16.14 inch
Internal Dimensions	W48.0 x H 37.7 x D 29.0 cm W18.9x H 14.84 x D 11.41 inch
Capacity	81L Up to 16 x 1kg 200mm spools (estimated)
Door	PVC Frame with Glass Door
Cabinet	High Quality Steel Airtight Cabinet
	Anti-rust Coating
Shelves	1 Adjustable Hanging Rod & 4 Filament Feed Ports for Direct Printing
Power Consumption	12W (avg.)
Voltage	110V/0.9A (220V are available upon request)
Hygrometer	Digital hygrometer Accuracy : ±3%RH (0~80%RH), ±0.3°C (20~40°C)

Instrument name: Testo 175-H2 38226481		Minimum	Maximum	Mean value	Limit values
Start time: 7/16/2020 2:09:16 PM		5.8	58.0	12.390	0.0/100.0
End time: 7/17/2020 4:29:16 PM	Humidity [%RH]				

