


Benchmark 

INCUSHAKE^R Series

Shaking Incubators

- + **Exceptional temperature uniformity**
- + **Miniature and cooling options available**
- + **Exchange flask clamps in one second with the new **MAGiC CLAMP™** magnetic system**



INCUSHAKE^R Mini



INCUSHAKE^R 10L/LR

WITH
**MAGiC
CLAMP**
PATENT PENDING





Incu-Shaker 10L
(H1010)

The new Incu-Shaker™ series of shaking incubators provide digitally regulated temperature with precisely controlled, circular (orbital) mixing, optimized for the culture of a wide variety of cell types.

The **Incu-Shaker Mini** is the most compact shaking incubator in its class. Despite the remarkably small footprint, a large 11.5 x 9.5 in. work space accepts several platforms for use with flasks up to 1 liter, tubes and other common vessels.

With similar features to the Incu-Shaker Mini, the **Incu-Shaker 10L and 10LR** models are equipped with a large 18 x 18 inch platform for high capacity applications. (See Chart for a complete listing of the maximum flask capacity.)


The standard platform (included with all three models) features a non-slip, rubber coated surface, ideal for tissue culture flasks, Petri dishes and staining trays. Convenient **MAGIC Clamp™** platforms, flask clamps and tube racks are also available for use with Erlenmeyer flasks and test tubes. This unique, magnetic attachment method is the easiest way to instantly change between flask clamps of different sizes. Each clamp utilizes a powerful (patent pending) magnetic base to securely attach the clamp to the shaking platform without the use of screws, bolts or tools.

Temperature, shaking speed and run time are displayed on the large LED control panel located on the front of the unit. The integral microprocessor includes a constant monitoring system that verifies and maintains accuracy through the duration of the program. Sophisticated over-temperature and over-speed controls ensure long life, safety and sample integrity.




Incu-Shaker Mini
(H1000-M)

Only 11" wide



H1010-P-MP



H1010-P-SP



H1000-MR-1550

Technical Data:

Temperature Range (Mini):	Ambient +5 to 70°C (Increments of 0.1°C)
Temperature Range (10L):	Ambient +5 to 60°C (Increments of 0.1°C)
Temperature Range (10LR):	Ambient -15 to 60°C (Increments of 0.1°C)
Temperature Uniformity:	+/- 0.25 %
Temperature Accuracy:	+/- 0.1 %
Shaking Speed Range:	30 to 300rpm (Increments of 1rpm)
Shaking Orbit:	19mm (3/4")
Platform Dimensions:	
Incu-Shaker Mini	9.5 x 11.5 in. / 23.5 x 29.2 cm
Incu-Shaker 10L/LR	17.8 x 17.8 / 45 x 45 cm
Exterior Dimensions:	
Incu-Shaker Mini	11 x 15.7 x 10.5 in. / 28 x 40 x 27 cm
Incu-Shaker 10L	20 x 26 x 19 in. / 51 x 65 x 47 cm
Incu-Shaker 10LR	20 x 31 x 22 in. / 51 X 79 X 56 cm.
Weight:	
Incu-Shaker Mini	25 lbs. / 11.5 kg
Incu-Shaker 10L	120 lbs / 55 kg
Incu-Shaker 10LR	170lbs / 78 kg
Electrical:	120 or 230V, 50-60Hz

Maximum capacity of Erlenmeyer flasks

Flask Size:	Incu-Shaker Mini	Incu-Shaker 10L/LR
50ml	20	49
125ml	12	36
250ml	8	25
500ml	5	16
1L	2	9
2L	0	5

Ordering Information

H1000-M* Incu-Shaker Mini, includes standard rubber mat platform, 115V
 H1010* Incu-Shaker 10L, includes standard rubber mat platform, 115V
 H1012* Incu-Shaker 10LR, includes standard rubber mat platform, 115V

*To order an item in 230V, add (-E) to item number.

Optional Platforms and Shelves

H1000-MR	MAGIC Clamp universal platform, for Incu-Shaker Mini (9.5x11.5")
H1010-MR	MAGIC Clamp universal platform, for Incu-Shaker 10L (18x18")
H1000-P-MP	Microplate platform, 4 position for Incu-Shaker Mini
H1010-P-MP	Microplate platform, 6 position for Incu-Shaker 10L
H1000-P-SP	Spring rack platform, holds uncommon vessels for Incu-Shaker Mini
H1010-P-SP	Spring rack platform, holds uncommon vessels for Incu-Shaker 10L
H1010-SH	Optional Shelf, for Petri Dishes, microplates, trays, etc. (14 x 5.5") for Incu-Shaker 10L (max. 3)

Flask & Tube Rack Accessories for MAGIC Clamp Platforms

H1000-MR-50	Flask Clamp, 50ml (H1000-MR: max. 20 / H1010-MR: max. 49)
H1000-MR-125	Flask Clamp, 125ml (H1000-MR: max. 12 / H1010-MR: max. 36)
H1000-MR-250	Flask Clamp, 250ml (H1000-MR: max. 8 / H1010-MR: max. 25)
H1000-MR-500	Flask Clamp, 500ml (H1000-MR: max. 5 / H1010-MR: max. 16)
H1000-MR-1000	Flask Clamp, 1000ml (H1000-MR: max. 2 / H1010-MR: max. 9)
H1000-MR-2000	Flask Clamp, 2000ml (H1010-MR: max. 5)
H1000-MR-MP	Microplate Clamp, (H1000-MR: max. 4 / H1010-MR: max. 6)
H1000-MR-1550	Tube Rack, 20x50 & 30x15 ml tubes (H1000-MR: max. 1 / H1010-MR: max. 4)
H1000-MR-T15	Tube Rack, 32x15 tubes (H1000-MR: max. 2 / H1010-MR: max. 8)
H1000-MR-T50	Tube Rack, 15x50 tubes (H1000-MR: max. 2 / H1010-MR: max. 8)
H1000-MR-T600	Bottle Rack, 4x500/600ml conical bottles (H1000-MR: max. 1 / H1010-MR: max. 2)
H1000-MR-TSR	Tilted holder for 15mL and 50mL tube racks

PO Box 709 Edison, NJ 08818
TEL: 908-769-5555 Fax: 908-222-1864
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com