



Meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541

Features

- Constructed from extruded honey-comb structure of high impact polypropylene material yielding superior strength and durability
- Provides physical protection with conductive material ensuring reliable path-to-ground
- Rolled over side construction (double thickness) for greater durability
- Identified with ESD protective symbol as required by ANSI/ESD S541
- Conductive plastic handle for ease of handling
- Includes steel wire frame for extra strength
- Chemical and moisture resistant
- Ideal use where corrugated and/or paper products cannot be used
- Product ships assembled
- Available options include: (1) Lid manufactured from ENDURA-TEK™; (2) Static Dissipative Foam bottom to provide ESD and shock protection
- Made in the United States of America

Specifications

Properties

Resin Type

Conductive

Surface Resistivity

Material Thickness

Melting Temperature

Heat Deflection

Typical Values

Polypropylene

Inherently

< 1 x 10⁴ ohms per ANSI/ESD STM11.11 and ESD TR53

4.0 mm

320° F

185° F

Per Packaging standard ANSI/ESD S54.1 section 6.1. Inside an ESD Protected Area "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact."

Part No.	Size I.D. - L x W x D (IN)	Size I.D. - L x W x D (MM)	Lid**	Foam**
39440	17 x 13 x 6-3/4	432 x 330 x 171	39470	37452
39441	17 x 13 x 8-3/4	432 x 330 x 222	39470	37452
39442	17 x 13 x 10-3/4	432 x 330 x 273	39470	37452
39443	18-3/8 x 12-3/8 x 12-3/4	467 x 314 x 324	39471	37454
39444	18-5/8 x 15 x 5-7/8	473 x 381 x 149	39472	37455
39445	18-5/8 x 15 x 8	473 x 381 x 203	39472	37455
39446	22-7/8 x 12-7/8 x 8	581 x 327 x 203	39473	37453
39447	22-7/8 x 12-7/8 x 18-1/4	581 x 327 x 464	39473	37453

** Lid and foam pad are sold separately



Made in the United States of America

Specifications and procedures are subject to change without notice

ENDURA-TEK™ STORAGE CONTAINERS

Unless otherwise noted, tolerances are ± 1/8"

PROTEKTIVE PAK

DRAWING NUMBER
39440

DATE:
March
2024