

Revision Number: 005.1

PRODUCT AND COMPANY IDENTIFICATION

Product name:

Adhes Product type/use: Cyano Restriction of Use: None i Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 480 INSTANT ADHESIVE, BLACK known as 480 Prism® Instant Adhesive, B Cyanoacrylate None identified

1.

IDH number:

234048

 Item number:
 48061

 Region:
 United States

 Contact information:
 Telephone: +1 (860) 571-5100

 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711

 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887

 Internet: www.henkelna.com
 Internet:

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	BONDS SKIN IN SECONDS.	
	COMBUSTIBLE LIQUID.	
	CAUSES EYE IRRITATION.	
	MAY CAUSE RESPIRATORY IRRITATION.	
	SUSPECTED OF CAUSING CANCER.	

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)	

Precautionary Statements

Prevention:	
	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.
Response:	
	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	
	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	
	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 234048

See Section 11 for additional toxicological information.

Product name: LOCTITE 480 INSTANT ADHESIVE, BLACK known as 480 Prism® Instant Adhesive, B Page 1 of 6

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Ethyl 2-cyanoacrylate	7085-85-0	80 - 100	
Carbon black - Nano	1333-86-4	1 - 5	
Phthalic anhydride	85-44-9	0.1 - 1	
Hydroquinone	123-31-9	0.1 - 1	

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.	
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apar using a blunt instrument. If skin is burned due to the rapid generation of hea by a large drop, seek medical attention. If lips are bonded, apply warm wate to the lips and encourage wetting and pressure from saliva in mouth. Peel o roll lips apart. Do not pull lips apart with direct opposing force.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond th adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.	
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.	
Symptoms:	See Section 11.	
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.	
5.	FIRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures	Moor a colf contained broothing apparetus with a full face piece appareted in	

Extinguishing mount	trace optay (rog), rearry ary enemical of carbon architer.
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Ventilate area. Do not allow product to enter sewer or waterways.
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

IDH number: 234048

Product name: LOCTITE 480 INSTANT ADHESIVE, BLACK known as 480 Prism® Instant Adhesive, B Page 2 of 6

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

For safe storage, store between 2 °C (35.6 °F) and 8 °C (46.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	1 ppm STEL 0.2 ppm TWA (Respiratory sensitization) (Dermal sensitization)	None	None	None
Carbon black - Nano	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Phthalic anhydride	0.005 mg/m3 STEL Inhalable fraction and vapor. 0.002 mg/m3 TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor. (Respiratory sensitization) (Dermal sensitization)	2 ppm (12 mg/m3) PEL	None	None
Hydroquinone	1 mg/m3 TWA (Dermal sensitization)	2 mg/m3 PEL	None	None

Engineering controls:

Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection:

Eye/face protection:

Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Use nitrile gloves and aprons as necessary to prevent contact. Do not use $\mathsf{PVC},\;\mathsf{nylon}\;\mathsf{or}\;\mathsf{cotton}.$

< 0.5 mm hg (25 °C (77°F)) < 700 hPa (50 °C (122°F)) no method / method

9. PHYSICAL AND CHEMICAL PROPERTIES

Sharp, Irritating

1.1 at 20 °C (68°F)

Liquid

Black

1 - 2 ppm

unknown

3 20 °C

Not available.

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure:

Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point:

Flammable/Explosive limits - lower:

Product name: LOCTITE 480 INSTANT ADHESIVE, BLACK known as 480 Prism® Instant Adhesive, B Page 3 of 6

> 149 °C (> 300.2 °F)no method / method unknown

80 - 93 °C (176°F - 199.4 °F) Tagliabue closed cup

Not applicable, Product reacts with water.

Not applicable, Product is a liquid

IDH number: 234048

Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature: Not available. 485 °C (905°F) The product is not flammable. Not available. Polymerises in presence of water. Miscible Not available. < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated) Not available. Not available.

Stability:		Stable under recommended storage conditions.
Hazardous	reactions:	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.
Hazardous products:	decomposition	None
Incompatib	le materials:	Water, amines, alkalis and alcohols.
Reactivity:		Not available.
Conditions	to avoid:	Spontaneous polymerization.
		11. TOXICOLOGICAL INFORMATION
Bolovant r	autos of oxposuro	Skin Inhalation Even

10. STABILITY AND REACTIVITY

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.
Skin contact:	Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.
Eye contact:	Irritating to eyes. Causes excessive tearing. Eyelids may bond.
Ingestion:	Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

Hazardous Component(s) LD50s and LC50s		Immediate and Delayed Health Effects
Ethyl 2-cyanoacrylate	None	Irritant, Allergen, Respiratory
Carbon black - Nano	Oral LD50 (Rat) = > 8,000 mg/kg	No Data
Phthalic anhydride	Oral LD50 (Rat) = 800 mg/kg Oral LD50 (Mouse) = 1,500 mg/kg Oral LD50 (Rat) = 1,530 mg/kg Oral LD50 (Rat) = 4,020 mg/kg Oral LD50 (Rabbit) = > 1,000 mg/kg Dermal LD50 (Rabbit) = > 3,160 mg/kg Inhalation LC50 (Rat, 4 h) = > 2.14 mg/l	Allergen, Corrosive, Irritant, Respiratory
HydroquinoneOral LD50 (Rat) = 320 mg/kgOral LD50 (Mouse) = 245 mg/kgOral LD50 (Rabbit) = 540 mg/kgDermal LD50 (Rat) = > 900 mg/kg		Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Immune system, Irritant, Liver, Mutagen, Skin, Thyroid

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	No	No
Carbon black - Nano	No	Group 2B	No
Phthalic anhydride	No	No	No
Hydroguinone	No	No	No

12. ECOLOGICAL INFORMATION			
Ecological information: Do not empty into drains / surface water / ground water.			
13	3. DISPOSAL CONSIDERATIONS		
In	formation provided is for unused product only.		
Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.		
1	4. TRANSPORT INFORMATION		
The transport information provided in th	his section only applies to the material/formulation itself, and is not specific to any packaging.		
U.S. Department of Transportation G Proper shipping name: Hazard class or division: Identification number: Packing group:	Ground (49 CFR) Combustible liquid, n.o.s. (Cyanoacrylate ester) Combustible Liquid NA 1993 III		
International Air Transportation (ICA Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	O/IATA) Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) 9 UN 3334 III Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.		
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None		
15	5. REGULATORY INFORMATION		
ed States Regulatory Information			
TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis		
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: CERCLA Reportable quantity:	Hydroquinone (CAS# 123-31-9). Immediate Health, Delayed Health, Fire, Reactive None above reporting de minimis. Hydroquinone (CAS# 123-31-9) 100 lbs. (45.4 kg)		
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or othe reproductive harm.		
ada Regulatory Information			
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.		
	16. OTHER INFORMATION		

Prepared by: Regulatory Affairs

Issue date: 01/19/2024

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.