

# STATICO

Global Supplier of Static Control & Cleanroom Products

541 Taylor Way, #1. San Carlos, CA 94070. USA. [www.statico.com](http://www.statico.com)

Tel.: (650) 592-4733. 1-800-261-4149. Fax: 650-508-0761. [sales@statico.com](mailto:sales@statico.com)

---

## *Product Specifications* *S1460* *Two Layer Rubber Matting*



### *Description*

The S1460 Series is a two-layer, high temperature, solder and chemical resistant rubber matting. This product is ideal for static free workstations where repair work and soldering is performed. The first layer, available in **Blue; Green; & Gray** Colors with Paper Finish, is a static dissipative work surface & the second layer, available only in Black with Diamond Finish, is a conductive one. The 1460 series provides the highest quality rubber matting in the industry. Meets ANSI-ESD S20.20-2014.

## Specifications

Colors	<b>Blue/Black; Green/Black &amp; Gray/Black</b>
Thickness	80 mils (2 mm)
Tensile Strength	1000 psi (min) , ASDM-D-412
Elongation @ Break	300% (min), ASDM-D-412
Durameter (Shore A)	60 min , ASDM-D-2240
Resistance from Surface To Groundable Point RTG	8 x 10 E6 ohms, EOS/ESD-S4
Resistance between Two Points on Surface, RTT	2 x 10 E7 ohms, EOS/ESD-S4
Charge Decay Time 5,000V to 50V	0.01 Seconds, FTMS 101C (Technical Zero) Method 4046C

### Standard Roll Sizes

- 24" x 50' x 0.080"
- 30" x 50' x 0.080"
- 36" x 50' x 0.080"
- 48" x 50' x 0.080"
- Cuts to special sizes are available upon request