

PolySWAB®

cleaning critical surfaces



Description

PolySWAB® 1500 and 1600 Series Swabs feature a patent-pending polyester fabric over foam tip thermally bonded to a polypropylene shaft resulting in a swab that is soft, conformable to work surface yet both resistant to abrasion and solvents. PolySWAB® is also available with tips fabricated from 100% fabric for applications requiring prolonged exposure to solvents such as Acetone, Ethyl Ether and NMP. Tip options include a heavy weight textured fabric for applications requiring streak-free cleaning.

The PolySWAB® 1600 Series employs a static dissipative handle for ESD sensitive applications.

Common Characteristics and Benefits

- ◆ Fabric over foam construction compatible with aggressive solvents such as Acetone, Kyzen and MEK
- ◆ Available in multilayer tips where softness and conformability are important.
- ◆ Textured fabric tips enable excellent removal of difficult to remove stains and particles.
- ◆ Proprietary cleaning process ensures low extractable for streak free cleaning.

Applications

- Cleaning stains and particles from scratch sensitive optics and optical assemblies
- Cleaning applications that require Acetone, MEK, NMP and Kyzen
- Cleaning blind surfaces such as O-ring grooves and ink jet print heads
- Removing excess materials in fine assembly operations

Physical Properties

Tip	Fabric Over Foam, Single Knit, Double Knit and Textured Polyester Fabric
Tip Bond	Thermal-Ultrasonic
Handle	Polypropylene and ESD Safe Polypropylene






www.foamtecintlwcc.com

USA +1.866.922.7160 +1.760.599.7160 fax +1.760.599.7322 Thailand +66.35740717 fax +66.35740744

Swab Models

Measured in Millimeters. ± 0.02

Product Name	HT1501T2	HT1530T	HT1541T2	HT1550T	HT1587T2	HT1601T2	HT1630FZ	HT1630T	HT1650FZ	HT1650T	
											
Head Material	PolyCLEAN®						CleanWIPE®	PolyCLEAN®	CleanWIPE®	PolyCLEAN®	
Head Thickness	2.9	1.6	3.2	2.2	3.5	2.9	2.2	1.6	2.3	2.5	
Head Width	6.3	3.7	4.0	2.3	15.3	6.3	3.6	3.7	2.4	2.3	
Head Length	17.0	10.5	10.0	10.5	23.0	17.0	10.2	10.3	10.5	10.5	
Handle Material	Polypropylene					Polypropylene with Permanent ESD Additive					
Handle Diameter	2.9	2.5	2.5	2.5	6.8	2.9	2.5	2.5	2.5	2.5	
Handle Length	134.3	62.7	57.8	58.1	103.5	134.6	59.2	62.7	57.9	57.9	
Total length	151.3	73.2	67.8	68.6	126.5	151.6	69.4	73.0	68.4	68.4	
Head Bond	Thermal										
Handle Color	Blue				White						
Tip Description	Flexible Cylinder	Flexible, Micro Paddle	Rigid, Mini Round	Pointed	Square Head	Flexible, Med. Cylinder	Flexible, Micro Paddle	Flexible, Micro Paddle	Semi-Flexible, Micro Spear	Semi-Flexible, Micro Spear	

Cleanliness

Particles (via LPC >.5µm) <3k per swab

NVR (mg/swab)

DI H₂O <.15
IPA <.40

Ionics (Via IC in mg/swab)

Chloride <.9
Sulfate <.4
Sodium <.7
Fluoride <.4
Nitrate <.2
Magnesium <.2

Free of Silicone/Amide

FOR TECHNICAL SUPPORT AND SITE TRAINING: Please contact our technical assistance services at +1.760.599.7160, +1.866.922.7160 or e-mail: info@foamtecintlwcc.com and our staff will arrange for a technical service engineer or a field sales engineer to assist you.



Rev. D

www.foamtecintlwcc.com

USA +1.866.922.7160 +1.760.599.7160 fax +1.760.599.7322 Thailand +66.35740717 fax +66.35740744