



\*Estimated  
 N/A-Not Applicable  
 N/R-Not Restricted  
 N/E-Not Established

TACKI PAK

# MATERIAL SAFETY DATA SHEET

<b>NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.</b>					
<b>IDENTITY</b> (As shown on Label or package) COR-COAT Part # 1278 SSD & Part #1234SC			<b>PART NO.</b> IF APPLICABLE		
<b>SECTION I</b>					
<b>MANUFACTURER'S NAME</b> Formulated Specifically for Conductive Containers, Inc.			<b>EMERGENCY PHONE No.</b> USA only: 1-800-424-9300 INT'L: 703-527-3887		
<b>ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)</b> 4500 Quebec Ave N., New Hope, MN 55428			<b>REVISION #</b>		
			<b>MANUFACTURER'S PHONE No. FOR INFORMATION</b> 1-763-785-2156		
			<b>DATE MSDS WAS PREPARED</b> August 4, 2009		
<b>SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.</b>					
<b>HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)</b>	<b>% Wt. (OPTIONAL)</b>	<b>CAS NO.</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>OTHER LIMITS RECOMMEND</b>
Toluene	28-31	108-88-3	200 ppm	50 ppm	None
Methyl Acetate	17-20	79-20-9	200 ppm	200 ppm	None
VM & P Naphtha	10-13	64742-89-8	300 ppm	300 ppm	None
Heptane	6-9	426260-76-6	500 ppm	400 ppm	None
Methyl Ethyl Ketone	5-7	78-93-3	200 ppm	200 ppm	None
Carbon Black, Amorphous	2-7	1333-86-4	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>	None
<b>SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS</b>					
<b>BOILING POINT</b> 133°F	<b>SPECIFIC GRAVITY</b> (H <sub>2</sub> O =1) 0.857- .868		<b>APPROXIMATE WEIGHT PER GALLON (LBS)</b> 7.15-7.24		
<b>VAPOR PRESSURE</b> 163 mmHg @ 20°C	<b>VAPOR DENSITY</b> (AIR = 1) Heavier than air		<b>EVAPORATION RATE</b> (BUTYL ACETATE =1) > 1.0		
<b>SOLUBILITY IN WATER</b> Insoluble	<b>% VOLATILE</b> 71-73%	<b>% VOC</b> 52.93-54.21%	<b>OTHER (IF ANY)</b> None		
<b>VOC LBS./GAL</b> 3.83-3.88					
<b>APPEARANCE AND ODOR</b> Clear, Characteristic Odor					
<b>SECTION IV-FIRE AND EXPLOSION HAZARD DATA</b>					
<b>FLASH POINT</b> 15°F (METHOD USED) TCC	<b>FLAMMABLE LIMITS</b>		<b>LEL</b> 0.9	<b>UEL</b> 16.0	
<b>EXTINGUISHING MEDIA</b> Carbon Dioxide, Dry Chemical, or Foam					
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.					
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> This material is flammable and may be ignited by heat, sparks, flame or static electricity.					
<b>HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION</b> Carbon Dioxide and/or Carbon Monoxide					
<b>EXPLOSIVE LIMITS</b> (% BY VOLUME IN AIR) 0.9 – 16.0					
<b>SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION</b>					
<b>HAZARD RATING</b> 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV			<b>National Fire Protection Association (NFPA)</b> <b>FIRE</b> <u>3</u> <b>REACTIVITY</b> <u>0</u> <b>HEALTH</b> <u>2</u> <b>SPECIAL HAZARDS</b> <u>None</u>		

SECTION VI - REACTIVITY AND STABILITY DATA			
STABILITY	UNSTABLE	STABLE X	CONDITIONS TO AVOID None
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide			
HAZARDOUS POLYMERIZATION	MAY OCCUR WILL NOT OCCUR	X	CONDITIONS TO AVOID May be ignited by heat, sparks, flame or static electricity.
SECTION VII - HEALTH HAZARD DATA			
ROUTES OF ENTRY	INHALATION?	Yes	SKIN? Yes INGESTION? Yes EYES? Yes
HEALTH HAZARDS	ACUTE	X	See Signs and Symptoms of Exposure below.
	CHRONIC	X	Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.
CARCINOGENICITY: IARC 2B			
SIGN AND SYMPTOMS OF EXPOSURE			
Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.			
Target Organs: CNS, CVS, PNS, Liver, Kidneys, Lungs, Respiratory System, Skin.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pre-existing Heart, Liver, Kidney and Lung disorders.			
EMERGENCY AND FIRST AID PROCEDURES			
Ingestion: Contact Physician or Poison Control Immediately.			
Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.			
Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.			
Skin: Wash with soap and water.			
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED			
Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.			
Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam or contain spills. If large spill, notify appropriate state and local agencies.			
WASTE DISPOSAL METHODS			
Dispose of product in accordance with local, county, state and federal regulations.			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE			
Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.			
Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene.			
OTHER PRECAUTIONS			
Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner in accordance with Governmental Regulations.			
SECTION IX - CONTROL MEASURES			
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration, use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.		PROTECTIVE GLOVES	
		Impervious Gloves	
VENTILATION	LOCAL EXHAUST	Supplemental (if needed)	VENTILATION
	MECHANICAL (GENERAL) To maintain exposure below PEL's		
EYE PROTECTION		OTHER PROTECTIVE CLOTHING OR EQUIPMENT	
Chemical splash goggles, or approved eye protection.		Chemical Apron/Eye bath/Safety Shower	
WORK HYGIENIC PRACTICES Wash thoroughly after handling.			
SECTION X - TRANSPORTATION INFORMATION (Optional)			
DOT PROPER SHIPPING NAME Coating Solution		DOT HAZARD CLASS 3	
DOT UN NUMBER UN 1139		DOT PACKING GROUP II	
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3	
IATA UN NUMBER UN 1139		IATA PACKING GROUP II	
SECTION XI - 313 SUPPLIER NOTIFICATION			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Toluene, Methyl Ethyl Ketone			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Michael N. Hindin