


# G3 Contact Cleaner

1632

Electrical contact cleaners remove oxidation, oil, and other contaminants from contacts, metal switches, motors, relays, generators, edge connectors, buss bars, circuit breakers, scales and sensors. These are used in electrical maintenance and to repair faulty contacts by removing insulative contamination. Techspray offers a variety of solvents and waterbased products that allow customers to match the right products with their cleaning needs. Choosing a strong, high quality product saves time and money. Grease and oil flow right off, reducing the time and materials needed to scrub off stubborn soils.





#### Non-flammable & economical

Patented non-flammable contact cleaner formulated to be powerful, yet economical. Eliminate brushing and scrubbing, saving time and materials.

- · Powerful cleaner
- Non-flammable
- Non-ozone depleting
- · Safe on electronics
- Rapid evaporation
- Zero residue
- · Safe on most plastics
- EPA SNAP approved
- · Dielectric strength 36.2 kv

### Specifications:

- . Boeing spec D6-17487 rev. P
- Ford Tox #167835

## **Product Packaging**

1632-16\$
G3 Contact Cleaner
16 oz
12 units/case



### **Technical Information**





#### **Chemical Composition**

CHEMICAL NAME	CAS#
1,1,1,2,2,3,4,5,5,5-decafluoropentane (HFC-4310mee)	138495-42-8
1,2-transdichloroethylene	156-60-5
Carbon dioxide	124-38-9

#### **Plastics & Rubber Compatibility**

MATERIAL NAME	RATING
ABS	Not compatible
Nylon	Excellent
Lexan	Not compatible
HDPE	Excellent
LDPE	Excellent
C. E. Phenolic	Excellent
РММА	Not compatible
POM	Excellent
PP	Excellent
PS	Not compatible
PTFE	Excellent
PVC	Excellent

# **Environmental Policy**

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

### Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: <a href="www.techspray.com">www.techspray.com</a>.





North America
Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
Email: tsales@techspray.com

Europe
ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
Email: info@itw-cc.com

<u>Countries Outside US</u>
Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2016 Techspray, A Division of ITW

